



NATURHOLZBODEN

Reitdorf 124  
A-5542 Flachau  
Tel: 06457/2685-0  
frizzo@weiss.at

Flachau, 10.02.2021

## Written Confirmation

We hereby confirm, that WEISS Natural Wood Flooring Boards (up to a board width of 169mm), in compliance with the respective standards (ÖNORM B 2218, DIN 18356, DIN 18560), are suited for installation over low-temperature radiant heated subfloor screeds, under the following specific conditions:

- Maximum allowable moisture content of the screed (Carbide-Moisture-Meter-Measurement):
  - Cementitious (concrete) screed 1,5% CM
  - Anhydrite (Calciumsulphate) screed 0,3% CM
- A heating-up protocol must be presented
- The temperature of the installed wooden flooring must not exceed a maximum of 26°C.
- The heating flow temperature must be limited to 35 ° C. In this way, temperature peaks can also be avoided in times of increased energy demand (e.g. when heating up).
- The relative humidity of the air (R.H.) must be of minimum 50% during the heating season.

Note: When installing solid wood floorings over radiant heated subfloors, an increasing occurrence of gaps must be expected.

  
Dipl.-Ing. Filippo Rizzo  
(quality assurance manager)  
WEISS GmbH · Reitdorferstr. 124 · A-5542 Flachau  
Telefon: +43 (0) 6457/2685-0 · Info@weiss.at